



Model RCB-3

Resistor Calibration Box



The Resistor Calibration Boxes (RCB) are used to verify and proof any High Voltage Insulation Testers. They can be utilized to calibrate all High Voltage Insulation Testers very accurately Analogues or Digitals.

Specifications

Resistance ranges (Ω)	1M. 10M. 100M. 1G. 5G. 10G. 100G. 500G.
Resistance tolerances	$\pm 1\%$ (F)
Tolerance	$\pm 25\text{ppm}/^\circ\text{C}$: 1M Ω . 2M Ω . 7M Ω . 10M Ω . 20M Ω . 30M Ω . 50M Ω . 100M Ω . 200M Ω . 500M Ω $\pm 100\text{ppm}/^\circ\text{C}$: 1G Ω . 2G Ω . $\pm 200\text{ppm}/^\circ\text{C}$: 5G Ω . 10G Ω . 20G Ω . 50G Ω . 100G Ω . $\pm 400\text{ppm}/^\circ\text{C}$: 200G Ω . 500G Ω $\pm 1000\text{ppm}/^\circ\text{C}$: 1T Ω
Max. working voltage	DC 10kV
Operating temperature	$-30^\circ\text{C}\sim 75^\circ\text{C}$
Power coefficient	Below 3W
Connecting terminals	Binding Post : Resistance circuit and guard
Dimensions	430(L) \times 324(W) \times 127(D)mm
Weight	Approx. 4140g



联系人：曾祥满 手机：13632925349 QQ：812401203 电话：0755-28896837

深圳众裕康科技有限公司
Shenzhen Zhong Yu Kang Technology Co., Ltd

地址：深圳市龙岗区沙平北路111号6008 网址：www.zykan.cn 邮箱：zykang2021@163.com